

2" Square Adjustable Ball Mounts (5/8" Pin Hole)

Part #	Class Rating	Capacity GTW	Capacity TW	Hole Size	Length	Rise	Drop
2528	III	6,000 lbs	600 lbs	1"	12 ³ / ₄ "	9 ⁵ / ₈ "	11"
1802310	IV	12,000 lbs	1,200 lbs	3 @ 1" 1 @ 1 ¹ / ₄ "	12 ¹ / ₈ "	6"	6"
2841AT	III	5,000 lbs	500 lbs	Adjustable while trailer is attached		6 ¹ / ₄ "	7 ¹ / ₂ "
2528-1	III	6,000 lbs	600 lbs	Replacement Ball Platform for #2528			
2529-1	IV	10,000 lbs	1,200 lbs	Replacement Ball Platform for #2529 (requires solid shank mount)			



Self-Locking MasterLock Ball Mount

Part #	Class Rating	Capacity GTW	Capacity TW	Note	Rise	Drop
3489AT	III & IV	6,000 lbs	600 lbs	Locking ball mounts w/locking pins built into shank. No separate pin or lock necessary	3/4"	2"
3490AT	III & IV	6,000 lbs	600 lbs		2"	4"

Pintle Mounts

(5/8" pin hole. For pintles w/(4) 1/2" bolt mounting)

Part #	Shank	Description	Capacity
2534	2" Solid	8 Holes, 6 ⁵ / ₈ " Face to Center of Pin	10,000 GVWR
2535	2" Solid	8 Holes, 9 ¹ / ₂ " Face to Center of Pin	10,000 GVWR
2539	2" Solid	14 Holes, 10 ¹ / ₈ " Face to Center of Pin	10,000 GVWR
45156	2 ¹ / ₂ " Tube	6 Holes, 7 ³ / ₄ " Face to Center of Pin	12,000 GVWR
45294	2 ¹ / ₂ " Forged	8 Holes, 8 ¹ / ₂ " Face to Center of Pin	18,000 GVWR



Solid Shanks

Part #	Length	Description
2505	12"	2" square with 5/8" pin hole. Pin hole center is drilled 2 ⁵ / ₈ " from one end of shank.
2519	24"	

Information

Hubs and Axles

Brake Assemblies

Suspensions & Fasteners

Tires & Wheels

Couplers, Jacks & Winches

Hitches & Towing Accessories

Body Components

Trailer Parts

Lights & Electrical

Locks & Cargo Control

Brake Actuating Systems

Switches